



F2

User Capacity Fingerprint Card	1000 500 500
Operating Voltage Idle Current Active Current	12VDC 20Ma <40Ma
Proximity Card Reader Radio Technology Read Range	Industry Standard 26 bits 125KHz Industry Proximity EM Card 1-4cm
Fingerprint Reader Resolution Identification time FAR FRR	Optical fingerprint Module 500DPI <1S <0.002% <0.0001%
Wiring Connections	Relay Output, Exit Button, DOTL, Alarm, Wiegand output
Communication	USB for downloading/uploading
Relay Adjustable Relay Output Time Lock Output Load Alarm Output Load	One (NO, NC, Common) 1-99 Seconds (5 seconds default) 2 Amp Maximum 5 Amp Maximum
Wiegand Interface	Wiegand 26 bits Format Output
Environment Operating Temperature	Indoor -15 °C ~ 60 °C (5 °F ~ 140 °F)

Operating Humidity	20%RH-90%RH
Physical Surface Finish Dimensions Unit Weight Shipping Weight	Zinc-Ally Enclosure Power Coat 13.5L x 5.4W x 2.4H (cm) 490g 650g

Metal case, one relay

- 500 fingerprint users & 500 card users
- Wiegand 26 bits output
- Pulse mode, toggle mode
- Anti-tamper alarm
- Integrated alarm & buzzer output
- Support U disk for downloading/uploading users information

Working Mode:



